# Select, Secure, Succeed.

FASTPro: Flexible Alignment System Technology



### Alignment Platform



Open Sealed



4-Hole

## Distal Adapter



**Tube Clamp** 



**Female Pyramid** 

Material

**ALUMINUM** 

**TITANIUM** 

# Select

There's a FASTPro solution for every situation with 3 proximal alignment options, 2 distal adapter options, and a choice of aluminum or titanium.

# Secure

FASTPro adapters provide exceptional flexibility in a compact design, featuring up to  $\pm 0.45$  inches of horizontal slide adjustment, up to  $\pm 12^\circ$  of angular adjustment, and a full 360° of rotation.

With all adjustment options in one adapter, it's easy to secure a quick and reliable fitting.





# **Open Lamination**

Selected for its versatility to switch between a female adapter and a tube clamp as needed. For use with flexible inner liner.







	Tube Clamp Adapter Aluminum	Tube Clamp Adapter Titanium	Tube Clamp Adapter Titanium, Small
Horizontal Slide	± 0.45 in. (11.5 mm)	± 0.45 in. (11.5 mm)	± 0.45 in. (11.5 mm)
Angle Adjustment	± 12°	± 10°	± 10°
Rotation	360°	360°	360°
Product Weight	8.6 oz. (245 g)	9.7 oz. (275 g)	8.5 oz. (240 g)
Build Height	1.3 in. (33 mm)	1.3 in. (33 mm)	1.1 in. (28 mm)
Weight Limit	275 lbs. (125 kg)	275 lbs. (125 kg)	275 lbs. (125 kg)
Warranty	12 months	12 months	12 months
Part Number	731163117	731162117	731162119





	Female Pyramid Adapter Aluminum	Female Pyramid Adapter Titanium
Horizontal Slide	± 0.4 in. (10 mm)	± 0.4 in. (10 mm)
Angle Adjustment	± 8°	±6°
Rotation	360°	360°
Product Weight	6.5 oz. (185 g)	7.8 oz. (275 g)
Build Height	0.87 in. (22 mm)	0.87 in. (22 mm)
Weight Limit	275 lbs. (125 kg)	275 lbs. (125 kg)
Warranty	12 months	12 months
Part Number	731163123	731162123

# Sealed Lamination

Preferred when the connection type is predetermined, simplifying the socket laminating process.









	Tube Clamp Adapter Aluminum	Tube Clamp Adapter Titanium	Female Pyramid Adapter Aluminum	Female Pyramid Adapter Titanium
Horizontal Slide	± 0.45 in. (11.5 mm)	± 0.45 in. (11.5 mm)	± 0.4 in. (10 mm)	± 0.4 in. (10 mm)
Angle Adjustment	± 10°	± 10°	± 8°	±6°
Rotation	360°	360°	360°	360°
Product Weight	9.3 oz. (256 g)	9.7 oz. (275 g)	7.1 oz. (200 g)	8.1 oz. (230 g)
Build Height	1.2 in. (31 mm)	1.34 in. (34 mm)	0.94 in. (24 mm)	0.87 in. (22 mm)
Weight Limit	275 lbs. (125kg)	275 lbs. (125 kg)	275 lbs. (125 kg)	275 lbs. (125 kg)
Warranty	12 months	12 months	12 months	12 months
Part Number	731163102	731162102	731163125	731162125

# 4-Hole Lamination

Ideal for any socket with a 4-hole connection.





	Tube Clamp Adapter Aluminum	Female Pyramid Adapter Aluminum
Horizontal Slide	± 0.45 in. (11.5 mm)	± 0.4 in. (10 mm)
Angle Adjustment	± 10°	± 8°
Rotation	360°	360°
Product Weight	9.95 oz. (282 g)	6.5 oz. (185 g)
Build Height	1.2 in. (31 mm)	1.14 in. (29 mm)
Weight Limit	275 lbs. (125 kg)	275 lbs. (125kg)
Warranty	12 months	12 months
Part Number	731163180	731163190



### **Fillauer LLC**

2710 Amnicola Highway Chattanooga, TN 37406 423.624.0946

## **Fillauer Europe**

Kung Hans Väg 2 192 68 Sollentuna, Sweden +46 8 505 332 00

© 2025 Fillauer LLC AD399/02-26-25