

Because
the world
isn't flat.



Motion Control
division of
Fillauer®

MOTIONFOOT® MX

from Motion Control



Features & Benefits

- Anatomically correct, 50 degree range-of-motion hydraulic ankle-foot
- Distinct heel design reduces shock and cushions initial heel contact
- Variable toe lever arm allows smooth, dynamic loading of the carbon foot plates
- Split-toe feature provides excellent inversion and eversion for compliance on rugged terrain

Specifications

Patient weight: Up to 220 lbs. (100 kg)

Foot weight: 28 oz. (795 gm) without foot shell

Build height: 4 inches with foot shell

Functional level: K2 – K4

Satisfaction Guarantee

60 days from the date of shipment

Warranty

- 2 years from the date of shipment
- Foot Shell: 6 months from the date of shipment

Ordering Information

Locate on the selection chart the patient's weight and foot size. A High Activity (HA) patient may require a higher weight range for increased stiffness.

Weight		22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
100-130 lbs	45-59 kg	5020020	5020022	5020024	5020026	5020030	--	--	--	--
131-161 lbs	59-73 kg	5020020	5020022	5020024	5020026	5020030	5020034	5020038	--	--
162-192 lbs	73-87 kg	5020021	5020023	5020025	5020027	5020031	5020035	5020039	5020042	5020046
193-220 lbs	87-100 kg	5020021	5020023	5020025	5020028	5020032	5020036	5020040	5020043	5020047
193-220 lbs HA	87-100 kg HA	--	--	--	5020029	5020033	5020037	5020041	5020044	5020048



Motion Control, Inc.
 115 N Wright Brothers Drive
 Salt Lake City, UT 84116, USA
 Phone 801.326.3434
 Fax 801.978.0848
 Toll Free 888.696.2767